

Reg. No: 001093

Issue: 1

Doc. Date: 10.2011

English Version

# SEQUESTON HPMA

## GENERAL

|               |                              |
|---------------|------------------------------|
| Chemical Name | Hydrolyzed Polymaleic Acid   |
| Appearance    | Brown, yellow viscous liquid |

## SPECIFICATIONS

| <u>Properties</u>                   | <u>Typical Value</u> |
|-------------------------------------|----------------------|
| Active Content, %                   | 48.0 – 50.0          |
| pH , 1% solution at 25 °C           | 2.0 – 3.0            |
| Density, g/cm <sup>3</sup> at 20 °C | 1.18 – 1.22          |
| Average Molecular Weight            | 350 - 700            |
| Viscosity, cps at 25 °C             | 10 - 60              |

## PACKING

250kg per UN approved PE drum

## APPLICATIONS

Scale inhibitors, used in oil field water treatment, cooling water and low-pressure boiler treatment, in heavy duty industrial cleaners.

## TRANSPORT INFORMATION

CORROSIVE LIQUID, ACIDIC  
UN3265 PACKING GROUP III

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

## WaterChem Pte Ltd

48 Toh Guan Road East, #02-149 Enterprise Hub, Singapore 608586  
Tel: +65 6465 3268 Fax: +65 6465 3269  
Email: [ronaldau@waterchem.sg](mailto:ronaldau@waterchem.sg)  
[www.waterchem.sg](http://www.waterchem.sg)