

Reg. No: 001397  
Issue: 1  
Doc. Date: 10.2011  
English Version

## SEQUESTON

# Copolymer 400

### GENERAL

**Copolymer 400** can be used as de-scaler and corrosion inhibitor in circulating cool water system and oilfield refill water system. It has good dispersion property for scale of calcium carbonate and calcium phosphate in circulating cool water system. Moreover it has good scale inhibition for barium sulphate, strontium sulphate and silica scale. The advantages of copolymer 400 are strong chlorine tolerance, stable to chemical and can apply into wide range of water quality.

Product Name	Copolymer 400
Chemical Name	Phosphonic group into carboxylic group
Appearance	Amber transparent liquid

### SPECIFICATIONS

<u>Properties</u>	<u>Typical Value</u>
Solid Content, %	48 -- 52
pH , (1% solution )	3.0 ±1.0
Density, g/cm <sup>3</sup> at 20 °C	1.15 – 1.35
Total phosphate (as PO <sub>4</sub> <sup>3-</sup> ), %	0.5 min

### PACKING

250kg net Plastic Drum or IBC drum.

Storage : Stable for ten months in well-ventilated warehouse, away from direct sunlight.

### APPLICATIONS

**Copolymer 400** can be used as scale control inhibitor and the optimal dosage is 5-20mg/L. It can be used together with the other organo phosphines, copolymers, zinc salt or BTA, to control scale.

### TRANSPORT INFORMATION

CORROSIVE LIQUID, ACIDIC  
UN3265 PACKING GROUP III

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

## WaterChem Pte Ltd

48 Toh Guan Road East, #02-149 Enterprise Hub, Singapore 608586  
Tel: +65 6465 3268 Fax: +65 6465 3269  
Email: [ronaldau@waterchem.sg](mailto:ronaldau@waterchem.sg)  
[www.waterchem.sg](http://www.waterchem.sg)