

# SEQUESTON 6000

## GENERAL DESCRIPTION

**SEQUESTON 6000** is an excellent scale inhibitor to prevent the formation of calcium phosphate, calcium carbonate and other inorganic minerals. Sequeston 6000 can stabilize corrosion inhibitors such as zinc, phosphates and phosphonates; and it is compatible with any zinc or phosphate formula. Moreover, it can effectively to disperse inorganic micro-particles without pH influence.

Chemical Name : Acrylates-organic compounds mixture

## SPECIFICATIONS

<u>Properties</u>	<u>Typical Values</u>
Appearance	Light amber liquid
Solid Content,%	42.0 - 44.0
pH, ( 1% water solution)	3.8 - 4.6
Density, g/cm <sup>3</sup>	1.21 ±0.02

## APPLICATIONS

**SEQUESTON 6000** can be used as scale inhibitor for cooling water and boiler water system. The optimal chemical dosage is 10-30mg/L. When using with other chemicals' formula, the dosage should be determined by experiment.

## PACKING

250kg per drum

## TRANSPORT INFORMATION

UN No. 3265, Class 3, PG III

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

## WaterChem Pte Ltd

48 Toh Guan Road East, #02-149 Enterprise Hub, Singapore 608586  
Tel: +65 6465 3268 Fax: +65 6465 3269  
Email: [ronaldau@waterchem.sg](mailto:ronaldau@waterchem.sg)  
[www.waterchem.sg](http://www.waterchem.sg)