

Reg. No: 001326
Issue: 1
Doc. Date: 10.2011
English Version

SEQUESTON Polymer 700

GENERAL

| | |
|-------------|--|
| Description | Polyacrylate polymer of low molecular weight |
| CAS No. | 9003-04-7 |
| Appearance | Clear, light amber liquid |

SPECIFICATIONS

| <u>Properties</u> | <u>Typical Value</u> |
|-------------------------------------|----------------------|
| Solid Content, % | 40.0 +/- 2 |
| pH , 1% solution at 25 °C | 7 +/- 1 |
| Density, g/cm ³ at 20 °C | 1.20 min |
| Viscosity at 30 °C, dL/g | 0.065-0.085 |
| Free Monomer (as Acrylic acid),% | 0.5 max |

PACKING

220kg per UN approved PE drum

APPLICATIONS

It is a general purpose antiscalant and it is suggested for use at a rate of 5 to 10 ppm dry for scale prevention in water systems of cooling towers, boilers, and heat exchangers.

TRANSPORT INFORMATION

Not regulated

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

WaterChem Pte Ltd

48 Toh Guan Road East, #02-149 Enterprise Hub, Singapore 608586
Tel: +65 6465 3268 Fax: +65 6465 3269
Email: ronaldau@waterchem.sg
www.waterchem.sg