

SEQUESTON 5000

GENERAL DESCRIPTION

SEQUESTON 5000 is an excellent scale inhibitor in industrial water system, paper maker, cooling water system, oil production applications etc. It can inhibit scale build-up on surfaces by dispersing calcium carbonate, calcium sulphate, barium sulphate and other salts in water system. Sequeston 5000 shows excellent freeze-thaw stability, moreover it can perform well in a wide range of pH, water hardness and temperature conditions.

Chemical Name : Mixture of polyacrylic acid compounds

SPECIFICATIONS

<u>Properties</u>	<u>Typical Values</u>
Appearance	Light amber liquid
Solid Content,%	46.0 - 50.0
pH, (1% solution)	3.1- 4.1
Density, g/cm ³	1.22 ±0.02

APPLICATIONS

The optimal dosage is 10-30mg/L.

PACKING

250kg per drum

TRANSPORT INFORMATION

UN No. 3265, Class 3, PG III

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

WaterChem Pte Ltd

48 Toh Guan Road East, #02-149 Enterprise Hub, Singapore 608586
Tel: +65 6465 3268 Fax: +65 6465 3269
Email: ronaldau@waterchem.sg
www.waterchem.sg